

BP LIFTS

By Barker Products 1310 Miller Road, Greenville, SC 29607 Phone:800-349-3149—Fax:864-297-1292



Model BPG-6145 LIFT



- Meets ANSI Z245 Type B Specifications
- Powered By a 2 1/2" Bore Hydraulic Cylinder With Cushions On Both Ends
- EZ Bolt On Kit Standard
- Hardened Steel Bearings For Long Life Cycle
- No Grease Points
- Can Not Be Hit By The Packer Blade
- · Kickout Feature Protects Lifter From Ground Damage
- Modular Bolted Construction For Ease Of Part Replacement
- Non Adjustable Lower Hook Linkage




BP LIFTS

By BARKER PRODUCTS 1310 Miller Road, Greenville, SC 29607 Phone:800-349-3149—Fax:864-297-1292



BPC-614SN40 ENVELOPE DIMENSIONS






BP LIFTS

BY BARKER PRODUCTS
1310 Miller Road, Greenville, SC 29607
Phone:800-349-3149—Fax:707-371-4886
WWW.BPLIFTS.NET



BPC-614SN Lift Unit Installation

- 1. Truck must be empty, clean and parked on a level surface before installation is started.
- 2. Remove all bumpers and running boards that will interfere with the location of the lift units. Relocate lower mounted tail lights as needed.
- 3. Measure and mark the centerline of the truck hopper. The centerline of the unit or units should be a minimum of 17" from the hopper centerline.
- 4. Hand valves should be mounted on the side of the hopper at the most convenient height for the operator and clear of the packer controls.
- 5. The top of the unit mounting plate should be tack welded in place at the height recommended on the envelope dimension sheet of the unit. CAUTION: SEE NOTE BELOW PICTURE
- 6. All dimensions should be approved by the customer before final welding.
- 7. If the mounting plate extends more than 2" above the hopper, a brace should be added.
- 8. Pressure must be set at 1200PSI minimum to 1400 maximum PSI.
- 9. Speed must be set to minimum 8 seconds total cycle time.



Mounting heights and locations are recommendations only. It is the responsibility of the installer to insure that the customer is satisfied with the height. Barker Products recommends that after the units are tacked in place, try the units with the can or cans the customer uses. The customer should approve your mount before final welding.








BU022XX-BPC-614SN LIFT UNIT WARRANTY

Barker Products warranties each new dump unit to be free of defects in material and workmanship under normal use and service for a period of 1 year or 2000 hours of operation, whichever comes first, from the date of delivery. Pressure must be set to 1200 to maximum 1400 PSI. Speed must be set to 8 seconds minimum complete cycle time.

This warranty excludes any obligations by BARKER PRODUCTS for the cost of down time. BARKER PRODUCTS will not warranty any dump unit which has been subject to misuse, neglect, alteration, or damaged by an accident.

On any work not performed by BARKER PRODUCTS or it's representitive, the customer will be responsible for freight charges on all parts shipped under warranty. Parts will be invoiced at time of shipment. Defective parts must be returned to BARKER PRODUCTS within 30 days. If the part is determined to be defective the customer will be credited for the original invoice.

Customer warranty labor charges must be approved by BARKER PRODUCTS in advance. If not contacted for approval, BARKER PRODUCTS will not be liable for the warranty labor charge.



| ITEM NO. | PART NUMBER | DESCRIPTION | QTY. |
|----------|-------------|-------------------------------|------|
| 1 | BWA17710 | MAINFRAME SUB ASSY 614SN | 1 |
| 2 | BWA17760 | LIFT ARM SUB ASSY 614SN | 1 |
| 3 | BW17730 | LEFT LP MOUNT 614S | 1 |
| 4 | BW17740 | RIGHT LP MOUNT 614S | 1 |
| 5 | BWA17460 | CYLINDER SUB ASSY | 1 |
| 6 | BW17780 | CYLINDER MOUNT PIN | 1 |
| 7 | XEB061000 | 3/8" LOCK WASHER | 1 |
| 8 | XAA081312 | 1/2-13 X 1 1/2 HHCS | 5 |
| 9 | BWA17850 | LIFT PLATE SUB ASSY 614S40 | 1 |
| 10 | BW17830 | HOOK LINK 614S40 | 2 |
| 11 | BW99108 | 1/2" SPHERICAL BEARING | 4 |
| 12 | XAE081310 | 1/2-13 X 1 1/4 FLANGED HHCS | 4 |
| 13 | XEA082412SS | FLAT WASHER 1/2 X 1 1/2 X 1/8 | 4 |
| 14 | XDA081300 | 1/2-13 HEX NUT | 4 |

| BARKER PRODUCTS 1310 MILLER ROAD GREENVILLE, SC 29607 |
|--|
|--|

DATE: 11/6/2018
MATERIAL: NOTED


DO NOT SCALE
DRAWING
UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL±1/32
ANGULAR: MACH±1° BEND ±1°
TWO PLACE DECIMAL ±0.010
THREE PLACE DECIMAL ±0.005

BPC-614\$N40 DE DRAWING NO BU02240 PARTS

REV 00

SCALE: 1:6 WEIGHT: 168.497 # SHEET 2 OF 2

| ITEM NO. | PART NUMBER | DESCRIPTION | QTY. |
|----------|-------------|-------------------------------|------|
| 1 | BW17710 | MAINFRAME 614S | 1 |
| 2 | BW17720 | BEARING MOUNT 614 | 4 |
| 3 | XEC0606080 | 3/8 HIGH COLLAR LOCK WASHER | 8 |
| 4 | XAB061612 | 3/8-16 X 1 1/2 SHCS | 8 |
| 5 | BW01110 | GREASE FITTING - 1/4-28 SHORT | 4 |
| 6 | BW99116 | SPHERICAL BEARING 1" | 4 |
| 7 | BW17525 | MOUNT PLATE - N | 1 |
| 8 | BW07140 | PLATE STUD | 5 |
| 9 | XDC082000 | 1/2-20 NYLOK NUT | 5 |





10/26/2018 DATE: MATERIAL: NOTED

DRAWING UNLESS OTHERWISE SPECIFIED: 614SN
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1° BEND ±1° TWO PLACE DECIMAL ±0.010 THREE PLACE DECIMAL ±0.005

MAINFRAME SUB ASSY


SCALE: 1:6

DRAWING NO REV BWA17710 00

WEIGHT: 67.973 #

SHEET 1 OF 1

| ITEM NO. | PART NUMBER | DESCRIPTION | QTY. |
|----------|-------------|------------------------------|------|
| 1 | BW17760 | LEFT LIFT ARM | 1 |
| 2 | BW17770 | RIGHT LIFT ARM | 1 |
| 3 | BW17750 | LIFT ARM SPACER | 2 |
| 4 | XEB161000 | 1" LOCKWASHER | 2 |
| 5 | XAB081312 | 1/2-13 X 1 1/2 SHCS | 4 |
| 6 | BW99030 | 1 7/8 CAM FOLLOWER | 2 |
| 7 | XDB161400 | 1"-14 HEX JAM NUT | 2 |
| 8 | XEB081000 | 1/2" LOCKWASHER | 4 |
| 9 | BW01115 | GREASE FITTING - 1/4-28 LONG | 2 |





3/18/2019 DATE: MATERIAL:

NOTED


DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED: 614SN
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1° BEND ±1° TWO PLACE DECIMAL ±0.010
THREE PLACE DECIMAL ±0.005

LIFT ARM SUB ASSY

DRAWING NO BWA17760 PARTS REV 00

SCALE: 1:4 SHEET 1 OF 1 WEIGHT: 20.364 #

| ITEM NO. | PART NUMBER | DESCRIPTION | QTY. |
|----------|-------------|------------------------------|------|
| 1 | BW17460 | HYDRAULIC CYLINDER 2 1/2 X 6 | 1 |
| 2 | BR05210 | 6801-06-06 ADAPTER | 1 |
| 3 | BV00062 | ORIFICE ADAPTER | 1 |
| 4 | BV00025 | 116 X 1/8 NPT ORIFICE PLUG | 1 |
| 5 | BW99116 | SPHERICAL BEARING 1" | 2 |
| 6 | XEA063212SS | FLAT WASHER 3/8 X 2 X 1/8 | 2 |
| 7 | XAE061606 | 3/8-16 X 3/4 FLANGED HHCS | 2 |






3/19/2019 DATE: MATERIAL: NOTED

DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED: 614SN
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1° BEND ±1° TWO PLACE DECIMAL ±0.010 THREE PLACE DECIMAL ±0.005

CYLINDER SUB ASSY

DRAWING NO REV BWA17460 00 SCALE: 1:4 SHEET 1 OF 1

WEIGHT: 13.907 #



| ITEM NO. | PART NUMBER | DESCRIPTION | QTY. |
|----------|-------------|------------------------------|------|
| 1 | BW17850 | LIFT PLATE | 1 |
| 2 | BW00800 | SADDLE | 1 |
| 3 | XAA061618 | 3/8-16 X 2 1/4 HHCS | 4 |
| 4 | XEB061000 | 3/8" LOCK WASHER | 9 |
| 5 | XDA061600 | 3/8-16 HEX NUT | 3 |
| 6 | XAH061620 | 3/8-16 X 2 1/2 CARRIAGE BOLT | 4 |
| 7 | BZ03451 | SUPPORT PLATE | 1 |
| 8 | BW17800 | TRFACK PLATE 614 | 2 |
| 9 | BW17790 | TRACK BAR 614 | 2 |
| 10 | BW17810 | TRACK CAP 614 | 2 |
| 11 | XDC081300 | 1/2-13 NYLOK NUT | 4 |
| 12 | BW17130 | HOOK BEARING MOUNT | 4 |
| 13 | XDC061600 | 3/8-16 NYLOK NUT | 4 |
| 14 | BW03195 | 12-DU-12 BEARING | 4 |
| 15 | BW03460 | hook shaft | 1 |
| 16 | BW07560 | WOODRUFF KEY #806 | 3 |
| 17 | BW07490 | HOOK | 1 |
| 18 | BW06780 | HOOK DRIVE | 2 |
| 19 | XEC0606080 | 3/8 HIGH COLLAR LOCK WASHER | 1 |
| 20 | XAB061612 | 3/8-16 X 1 1/2 SHCS | 2 |
| 21 | XAH081328 | 1/2-13 X 3 1/2 CARRIAGE BOLT | 4 |
| 22 | XAA061610 | 3/8-16 X 1 1/4 HHCS | 3 |
| 23 | XAB061610 | 3/8-16 X 1 1/4 SHCS | 1 |



10/30/2018 DATE: MATERIAL: NOTED

DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED: 614S40
DIMENSIONS ARE IN INCHES
TOLERANCES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1° BEND ±1° TWO PLACE DECIMAL ±0.010 THREE PLACE DECIMAL ±0.005

LIFT PLATE SUB ASSY

SCALE: 1:4

DRAWING NO REV BWA17850 PARTS 00

WEIGHT: 59.374 #

SHEET 2 OF 2